



## INSTRUCTIONS

### Bike Cover for Ladder Mounted Bike Rack (BC1250)

**STOP!!** If you have any questions, comments or problems installing this cover, or need to purchase extra parts, please call Top Line Manufacturing, Inc. at (800) 653-0605 or (562) 633-0605 (Mon-Fri 8a.m.-5p.m.). You may also e-mail us at: [toplinetechsupport@worldnet.att.net](mailto:toplinetechsupport@worldnet.att.net)


Enclosed in Bike Storage Bag:

- (1) Bike Cover
- (1) 95" Strap with Snap-buckle
- (3) Self-adhesive Black Plastic Pads

**IMPORTANT: Mount and strap BIKE RACK to the motorhome ladder according to the BIKE RACK instructions. DO NOT MOUNT BICYCLES ON THE RACK AT THIS TIME (The BIKE COVER must be placed on the rack BEFORE the bikes are mounted).**

1. Unzip Bike Cover. (FIG. B) shows the orientation of the cover.
2. Position the rectangular opening on the back of the bike Cover (FIG. A) over both arms of the Bike Rack (FIG. C).
3. Place bicycles on the rack. Strap bicycles to the rack according to the standard bike rack installation procedures on your "BIKE RACK INSTRUCTIONS". **NOTE:** Follow these same steps regardless of the position (left or right) of the bicycles' front wheel/handlebars.
4. Pull cover over the bikes, starting at the top.
5. Thread the 54" strap (this strap came with your bike rack) through the two 1/2" holes (grommets indicated on FIG. A) around the rear wheel axle of the bikes and the motorhome ladder. Install this strap according to the Bike Rack instructions.
6. Using the three self-adhesive black plastic pads (included), peel the backing off and adhere to the inside of the axle of the inner bike, pedals and handlebars. Additional pads may be purchased separately.
7. Zip cover closed so that the two zipper pulls meet at the bottom.
8. Place 95" strap around the bike cover (FIG. B), snap buckles together and pull strap tight.

BACK  
VIEW




Grommets (air circulation only)

FRONT  
VIEW



FIG. C



Rack Arms

**CAUTION!!** After you have loaded your bikes and zipped the cover closed, check to be sure that you can see the rear taillight, break lights, turn signals and license plate from behind your vehicle. If any of these is obscured, adjust the rack, bikes or cover immediately. When necessary, wiring and brake controller must be installed (ask your RV Dealer or RV Accessories Retailer).